

ZH506Te

High brightness professional laser projector



- **Bright FullHD 1080p laser projector - 5500 ANSI Lumens**
- **30,000 hours maintenance-free laser light source at full brightness**
- **Small lightweight chassis**
- **4K, HDR compatible**

The ZH506Te projector is more convenient than ever with a longer life and a smaller, lighter chassis than ever before. The 4K and HDR compatible, the ZH506Te is a low maintenance projector with extremely long-life laser technology at an impressive 5500lms.



Specifications

Display/imagen	
Tecnología de visualización	DLP
Resolución	1080p Full HD (1920x1080)
Brillo	5.500 lumens
ANSI Brillo	5.500 lumens
Ratio de contraste	300.000:1
Relación de aspecto nativo	16:9
Ratio de aspecto - compatible	4:3,16:9,16:10
Corrección Keystone - Horizontal	+/-30°
Corrección Keystone-Vertical	+/-30°
Corrección Keystone vertical automática	Yes
Reproducción de color (milliones)	1073.4
Frecuencia de muestreo horizontal	15.375 ~ 91.146 KHz
Frecuencia de muestreo vertical	50 ~ 85 Hz (120Hz for 3D)Hz
Uniformidad	85%
Tamaño de pantalla	0.72m ~ 7.62m (28.3" ~ 300") (diagonal)

Info Lámpara	
Fuente de luz	Laser
Vida del LÁSER	30.000horas

Óptica	
Distancia de tiro	1.4:1 - 2.24:1
Distancia de proyección (m)	1m - 10m
Zoom	1.6
Tipo de zoom	Manual
Distancia focal (mm)	20.91 ~ 32.62
Lens shift	Vertical -103 ~ 118%, Horizontal: +/-0%
Offset nativo	103%
Lens shift	Yes - {{downloads_link}}

Conectividad	
Conexiones	Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a / 3D , 2 x VGA (YPbPr/RGB), 1 x Video compuesto, 1 x RS232, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x 12V trigger, 1 x S-Video, 1 x RJ45 Outputs 1 x VGA, 1 x USB-A power 1.5A, 1 x Audio 3.5mm

General	
Nivel sonoro (tipico)	28dB
Compatibilidad PC	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilidad 2D	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Compatibilidad 3D	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
3D	
Seguridad	Security bar, Kensington Lock, Password protected interface
idiomas OSD / display	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operatividad 24/7	Yes
Operatividad 360°	Yes
Condiciones de funcionamiento	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Control remoto	Mando ProAV retroiluminado
Altavoces	2
Wattios por altavoz	10W
Contenido caja	AC power cord Remote control 2x AAA batteries Basic user manual

Networking	
LAN - control	Yes

Corriente	
Fuente de alimentación	100V ~ 240V, 50-60Hz
Consumo energético (standby)	<0.5W
Consumo energético (mín.)	190W
Consumo energético (máx.)	341W

Peso y dimensiones	
Peso	5.5kg
Dimensiones (W x D x H)	374 x 302 x 117

Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 20082019010939

