

X402

Bright, powerful and business ready



- **Bright XGA projector – 4200 ANSI lumens**
- **Crestron RoomView® – RJ45 control and monitoring**
- **Easy connectivity – HDMI, VGA and built-in 10W speaker**
- **Lightweight and portable - Carry bag included**

Project bright vibrant widescreen presentations any time of day. Designed for meeting rooms and classrooms, the X402 boasts a long lamp life and energy-saving features which provide a low overall cost of ownership.

This projector has a built-in speaker, networking capabilities, Full 3D technology and HDMI connectivity. It is also lightweight so can be installed or taken on the move in the handy carry bag for off-site meetings.



Specifications

Display/image	
Display technology	DLP
Resolution	XGA (1024x768)
Brightness	4,200 lumens
Contrast ratio	20,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - horizontal	+/-0°
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.3 ~ 91.1KHz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	0.78m ~ 7.8m (30.8" ~ 307") (diagonal)
Lamp info	
Light source type	Lamp
Lamp watts	260
Lamp life (hours)	3000 (Bright), 5500 (Dynamic), 5000 (Eco), 7000 (Eco+)
Optical	
Throw ratio	1.6:1 - 1.92:1
Projection distance (m)	1.2m - 12m
Zoom	1.2
Zoom type	Manual
Focal length (mm)	18.2 ~ 21.9
Native offset	115%
Connectivity	
Connections	<p>Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB/wireless), 1 x VGA (YPbPr/RGB), 1 x Composite video, 2 x Audio 3.5mm</p> <p>Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm</p> <p>Control 1 x RS232, 1 x RJ45, 1 x 3D sync, 1 x mini USB mouse/service</p>
General	
Noise level (typical)	31dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar,Kensington Lock,Password protected interface
OSD / display languages	21 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,German,Greek,
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	10W
In the box	Carry bag AC power cord Remote control 2x AAA batteries Basic user manual
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	257W
Power consumption (max)	306W
Weight and dimensions	
Net weight	2.57kg
Dimensions (W x D x H) mm	315 x 224 x 102



e