

W355

Bright, powerful and small



- **Bright WXGA projector – 3600 ANSI lumens**
- **Installation flexibility – 1.3x zoom**
- **Ultimate Control - Full support for Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **Easy connectivity - 2x HDMI, MHL, VGA, USB Power, 16W speaker**

Make your presentations count regardless of the ambient light level using the W355. Designed for education and business environments this powerful projector is perfect for installation with a wide zoom range, networking and control features. It also has long lamp life and energy-saving features to provide you with a low overall cost of ownership.



Specifications

Display/image	
Display technology	DLP
Resolution	WXGA (1280x800)
Brightness	3,600 lumens
Contrast ratio	22,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	16:9, 16:10
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.3 ~ 91.1KHz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0.92m ~ 7.65m (36.1" ~ 301.1") (diagonal)
Lamp info	
Light source type	Lamp
Lamp watts	195
Lamp life (hours)	5000 (Bright), 7000 (Dynamic), 6000 (Eco), 8000 (Eco+), 10000 (Education)
Lamp life (education)	10,000 hours
Optical	
Throw ratio	1.19:1 - 1.54:1
Projection distance (m)	1.2m - 7.7m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	16.91 ~ 21.6
Native offset	112%
Connectivity	
Connections	<p>Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 2 x VGA (YPbPr/RGB), 1 x S-Video, 1 x Composite video, 2 x Audio 3.5mm, 1 x Mic 3.5mm</p> <p>Outputs 1 x VGA (YPbPr/RGB), 1 x USB-A power 1A, 1 x Audio 3.5mm</p> <p>Control 1 x RS232, 1 x RJ45</p>
General	
Noise level (typical)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	16W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	187W
Power consumption (max)	225W
Weight and dimensions	
Net weight	2.51kg
Dimensions (W x D x H) mm	298 x 230 x 96

