

FHD153169

Fully optimised HD LED display – 3 x 1.69m (136" diagonal)



- **High calibre, high-resolution indoor Full HD LED display**
- **Easy installation and maintenance – surface mount and front access**
- **Ultra-thin panel depth - discreet, space-saving design**
- **Best in class processing and switching – HQUltra technology**

Optoma is the one-stop solution provider for projection and LED displays with its range of 4K UHD, Full HD and custom LED displays.

The ultra-thin, 16:9 native aspect ratio Full HD LED displays blend discretely into any corporate, higher education, hospitality and digital signage environment.

Easy to install, operate and maintain, they are designed for ultimate reliability and superior image quality.



Specifications

Screen	
Screen resolution	1080p Full HD (1920x1080)
Screen size (diagonal)	136"
Screen size	3000 x 1690
Minimum viewing distance	1.5m
Brightness (before calibration)	650 nits
Brightness (after calibration)	650 nits
Contrast	4000:1
Dimensions (W x D x H) mm	3000 x 54 x 1690
Net weight	154.8kg
Screen processing	
Scaler-switcher	LS200T
Sender	MCTRL660
LEDs	
Pixel pitch (H x V)	1.562mm
LEDs per pixel	1R1G1B
Red wavelength (dominant)	620nm
Green wavelength (dominant)	520nm
Blue wavelength (dominant)	465nm
Pixels	
Pixel configuration	SMD 3-1
LED face colour	Black
LED size	SMD1010
Pixel resolution (width)	320 pixels/module
Pixel resolution (height)	180 pixels/module
Pixels per area	409,600 pixels/m ²
Module	
Active module width	3,000mm
Active module height	1,690mm
Standard active module area	0.1406m ²
Viewing angle - horizontal	>160°
Viewing angle - vertical	>160°
Ingress protection (front)	IP43
Ingress protection (back)	IP21
LED fixings	Front access
Storage temperature range	-10 - +50°C
Operating conditions	10 - 90 non-condensing
Operating temperature (min)	-10°C
Operating temperature (max)	50°C
Colour	
Greyscale processing depth	16 bits
Number of colours	281 (trillions)
Refresh rate	>3660 Hz
Brightness	
Brightness (before calibration)	650nits
Brightness (after calibration)	650nits
Contrast ratio	4,000
Brightness control levels	256
Power	
Input power (max)	60watts per panel
Power supply	110-240
Other	
Mechanical alignment adjustment	x/y/z (x/y/z planes)
Mitering	-90°
Mounting frame	Optional
Connectivity	
Connections	Inputs 2 x HDMI UHD 4K, 1 x HDMI FHD 1080P, 1 x DVI/HDMI, 1 x HDBaseT 4K, 1 x DisplayPort 4K, 1 x Component input via DVI-U, 1 x Composite video, 2 x 3G-SDI, 1 x VGA, 1 x RJ45 streaming, 2 x Microphone, 6 x Stereo analogue audio Outputs 1 x DVI/HDMI, 1 x HDMI UHD 4K, 1 x HDBaseT 4K, 1 x Speaker Control 1 x RS232, 1 x RJ45