

W304M

Professional presentations on the move



- **Small, lightweight and portable**
- **Bright WXGA projector – 3100 ANSI lumens**
- **Easy connectivity - HDMI, VGA and built-in speaker**
- **Full 3D**

Ideally partnered with a widescreen notebook, HD sources or a mobile device, the W304M delivers bright vivid presentations and videos in the office or on the road.

Weighting only 1.4kg this travel-friendly projector incorporates a staggering 3100 ANSI lumens allowing you to project bright, crystal clear presentations during the day, leaving your audience speechless every time the projector is turned on.



Specifications

Display/image	
Display technology	DLP
Resolution	WXGA (1280x800)
Brightness	3,100 lumens
Contrast ratio	10,000:1
Native aspect ratio	4:3
Aspect ratio - compatible	16:9, 16:10
Keystone correction - vertical	+/-30°
Horizontal scan rate	15 ~ 91.4Khz
Vertical scan rate	43 ~ 87(120 for 3D)Hz
Uniformity	85%
Screen size	0.8m ~ 7.71m (31.65" ~ 303.44") (diagonal)
Lamp info	
Light source type	Lamp
Lamp watts	220
Lamp life (hours)	4000 (Bright), 5000 (Eco)
Optical	
Throw ratio	1.53:1 - 1.76:1
Projection distance (m)	1.2m - 10m
Zoom	1.15
Zoom type	Manual
Focal length (mm)	21.3 ~ 24.5
Native offset	114%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB/wireless), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm Control 1 x USB-B mouse/service
General	
Noise level (typical)	33dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	1W
In the box	Carry bag Lens cap AC power cord Remote control 2x AAA batteries Basic user manual
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	230W
Power consumption (max)	280W
Weight and dimensions	
Net weight	1.4kg
Dimensions (W x D x H) mm	220 x 178 x 71



1,